

HydraCutter C150™



HydraCutter C150™

Features & Benefits

- ▶ Makes clean plunge, bottom, notch, trim, and corner cuts without over cutting.
- ▶ Equipped with a powerful hydraulic motor that requires 8 gpm @ 2000 - 2500 psi.
- ▶ The trigger lockout safety feature is standard.
- ▶ Dual function trigger starts and stops saw and water simultaneously.
- ▶ Water flow system delivers maximum lubrication, cooling, and abrasive flushing through ten internal bar channels.
- ▶ A roller nose sprocket maximizes chain and bar life.
- ▶ Tapered bar design transmits increased power to the nose, reducing chain wear during plunge cuts.
- ▶ 20 in. bar provides a full 20 in. cutting depth.
- ▶ 15 in. bar provides a full 15 in. cutting depth.
- ▶ Choose from two diamond segmented chains:*
 - SL25 chains cut medium-soft to very hard aggregate with moderate to heavy steel reinforcing.
 - SL45 chains cut green concrete, brick and concrete block without steel reinforcing.
- ▶ 88 diamond cutting segments are laser welded to high carbon steel chain for use with the 20 in. bar.
- ▶ 76 diamond cutting segments are laser welded to a high carbon steel chain for use with the 15 in. bar.
- ▶ Ergonomic design with cushioned handles and balanced weight distribution enhances precision cutting with minimal force.
- ▶ Steel tube frame is durable, yet lightweight, resulting in less operator fatigue.
- ▶ RGC HydraCutter C150™ carrying case included.

HydraCutter C150™

The RGC HydraCutter C150™ is the original concrete cutting chain saw with years of proven performance. It is the tool of choice for virtually any difficult cutting situation.

This rugged, versatile handheld hydraulic chain saw makes clean, fast, precise straight cuts. A variety of chains and bars are available to cut through concrete, masonry, stone and other aggregates up to 20 in. thick.

The C150™ can be powered by one of the RGC HydraPaks or by any other compatible power source.

Specifications

Model	C150™ w/ 15 in. Bar	C150™ w/ 20 in. Bar
Cutting Depth	15 in. (38.1 cm)	20 in (50.8 cm)
Bar Size (approx.)	22-1/4 in. x 4 in. (55.9 cm x 10.2 cm)	26-1/2 in. x 4 in. (66.5 cm x 10.2 cm)
Flow	8 gpm (30 lpm)	8 gpm (30 lpm)
Pressure Range	2000 - 2500 psi (138 -172 bar)	2000 - 2500 psi (138 -172 bar)
Water Flow	2.5 gpm @ 50 psi (9.5 lpm @ 3.5 bar)	2.5 gpm @ 50 psi (9.5 lpm @ 3.5 bar)

Diamond Segmented Chains

Application	C150™	MiniSaw
For cutting medium-soft to very hard aggregate with moderate to heavy steel reinforcement.	SL25-76 (15 in. Bar)	SL25-50 (13 in. Bar)
	SL25-88 (20 in. Bar)	SL25-55 (15 in. Bar)
For cutting green concrete, brick and concrete block without reinforcement.	SL45-76 (15 in. Bar)	SL45-50 (13 in. Bar)
	SL45-88 (20 in. Bar)	SL45-55 (15 in. Bar)



P.O. Box 681 • Buffalo, NY • 14240-0681
 Phone: (716) 895-1156 • Fax: (716) 895-1547
Toll Free: 800-RGC-TOOL (742-8665)
 Web: www.rgcproducts.com

RGC Construction Products Are Distributed By: